

Hole Expansion Tools & Sets

BRIDGE REAMERS & STEP REAMERS

Type 54-UB -Straight Flute Type 55-UB -Spiral Flute

Bridge Reamers - Straight & Spiral Flutes - Taper Shank High-Speed Steel, Surface Treated

• These special Hi-Tungsten tool steel reamers with gold surface treated body

and clearance are designed to be used with Taper shank equipment.

• They are available in both straight and spiral flute configuration and are designed for heavy-duty reaming as encountered in the fabrication of structural steel assemblies, bridge erection, and ship construction.

	TYPE 54	4-UB S	TRAIGHT	FLUTE	
Part #	Diameter Inches	Flute Length	Overall Length	Morse Taper	Qty. per/pack
81630	7/16"	4-3/8	8-1/4	#2	1
81640	1/2"	5-1/8	9	#2	1
81650	9/16"	5-1/8	9	#2	1
81660	5/8"	6-1/8	10	#2	1
81670	11/16"	7-1/8	11-3/4	#3	1
81680	3/4"	7-3/8	12	#3	1
81690	13/16"	7-3/8	12	#3	1
81700	7/8"	7-3/8	12	#3	1
81710	15/16"	7-3/8	12	#3	1
81720	1"	7-3/8	12	#3	1
81730	1-1/16"	7-3/8	12	#3	1
81740	1-1/8"	7-3/8	12	#3	1
81750	1-3/16"	7-3/8	12	#3	1
81760	1-1/4"	7-3/8	13	#4	1
81770	1-5/16"	7-3/8	13	#4	1

Type 51-UBM

Car Reamers - Fast Spiral Hole Buster™ Super Premium Mechanics Length 3-Flats on Shank

· For use in enlarging previously formed or drilled holes.

 These reamers are especially designed for the reaming of structural steel plates commonly found in truck frames, rail cars, bridges, and pressure vessels.

|--|

Part #	Diameter Inches	OAL Inches	Point Diameter	Min. Starting Hole Size	Qty. per/pack
82100	3/8"	4.160	.183	3/16"	1
82120	1/2"	4.625	.245	1/4"	1
82140	5/8"	5.200	.310	5/16"	1
82170	3/4"	5.750	.370	3/8"	1

Type VT&R-8P

VORTEX-POINT & Car Reamers Mechanics Length

- **VORTEX**-POINT[™] Split-point design gives accurate starting and its self-centering eliminating the need for the use of a center punch.
- VORTEX-POINT[™] Unique tip geometry reduces heat generation & cutting tool wear increasing tool life.
- **Type 51-UBM** Mechanics Length reamers are especially designed for the reaming of structural steel plates commonly found in truck frames, rail cars, bridges, and pressure vessels.

uces heat ool life. are ctural s, rail	

Set	8 Pc. Ultra Dex	
Part #	3/16", 1/4", 5/16", 3/8" + 3/8", 1/2", 5/8", 3/4"	Qty of ea.
82340	VORTEX-POINT™ + Fast Spiral Car Reamer Type 250-VT & 51-UBM	1

TYPE 55-UB SPIRAL FLUTE						
Part #	Diameter Inches	Flute Length	Overall Length	Morse Taper	Qty. per/pack	
83310	7/16"	4-3/8	8-1/4	#2	1	
83320	1/2"	5-1/8	9	#2	1	
83330	9/16"	5-1/8	9	#2	1	
83340	5/8"	6-1/8	10	#2	1	
83350	11/16"	7-1/8	11-3/4	#3	1	
83360	3/4"	7-3/8	12	#3	1	
83370	13/16"	7-3/8	12	#3	1	
83380	7/8"	7-3/8	12	#3	1	
83390	15/16"	7-3/8	12	#3	1	
83400	1"	7-3/8	12	#3	1	
83410	1-1/16"	7-3/8	12	#3	1	
83420	1-1/8"	7-3/8	12	#3	1	
83430	1-3/16"	7-3/8	12	#3	1	
83440	1-1/4"	7-3/8	13	#4	1	
83450	1-5/16"	7-3/8	13	#4	1	

Type 78-GR -Gold Oxide Type 78-ZR -White Gold & SETS HSS Step Reamers, 3-Flats on Shank

- Accurately starts, enlarge and deburrs in holes in material up to 1/2" thick.
- 90° notch point starts holes easily.
- Each reamer has five hole enlargement steps.

Gold Oxide - low temperature stress relief that enhances lubricity, reduces friction and increases toughness. **Zirconium Nitride -** cutting machining aluminum magnesium, titanium alloys. Increased lubricity.



TYPE 78-GR GOLD OXIDE & TYPE 78-ZR WHITE GOLD

78-GR Gold Oxide Part #	78-ZR Zirconium Nitride Part #	Hole Sizes	Range	Shank Sizes	Step Thickness
83710	99940	5	5/16" - 9/16"	3/8"	1/2"
83720	99950	5	9/16" - 13/16"	3/8"	1/2"
83730	99960	5	13/16" - 1-1/16"	3/8"	1/2"
			SETS		

78-GR Part #	78-ZR Part #		Hole Sizes	Range	Shank Sizes	Step Thickness
83750	99980	3pc.	5	5/16" - 1-1/16"	3/8"	1/2"
83760	99990	2pc.	5	5/16" - 9/16"	3/8"	1/2"





Proudly Manufactured in the U.S.A • America's Finest High Speed Steel Cutting Tools[™]

www.vikingdrill.com

Fools[™] • Call Toll Free **1.800.328.4655**